



# KOTZUR

## TRANSPORTABLE SEALED GASTIGHT SILOS



A family  
owned  
Australian  
business



### APPLICATION

General purpose grain storage.

Medium/long term grain storage with phosphine or controlled atmosphere.

As a “hospital” silo for pest eradication of infested grain.

Ask for further information on the importance of sealed gastight silos in the drive to control insects and maintain grain free of chemical residue.

Optional Features include:

- Roof side inspection hole
- External wall roof ladder and cage
- Aeration
- Colorbond walls and roof

Standard Features include:

- Fumigation system
- Base manhole

### FEATURES

- Fully factory assembled and delivered ready to use.
- Kotzur Silos are manufactured to Silo Sealing Standard AS 2628 (sealed to 5 minute half pressure decay standard).
- Reliable pest eradication without chemical residues and risk of failure due to insect resistance to contact pesticides.
- Zincalume walls/roof and galvanised hopper/support structure.
- Auto resealing ground operated centre lid opening.
- Roof hatches lock down with a quick lever action and seal with a heavy duty O-ring seal.
- Outlet slide gate is sealed with a quick action, secondary seal plate. This allows resealing even when there is grain in the silo.
- Bin is pressure protected with high capacity oil bath relief valve.
- Sealants (e.g. silicone) are NOT required each time silo is sealed.
- Bin walls/roof are sealed using PVC and Silicone between the joints at time of construction to ensure a lifetime structural seal.
- All silo models can be tailored to specific customer requirements.
- Covered by Kotzur 5 year warranty.

SPECIFICATIONS (WALLA WALLA) Effective 14 August 2025

| MODEL     | CAPACITY<br>M <sup>3</sup> | CAPACITY<br>WHEAT<br>T <sup>(1)</sup> | MAX<br>LOAD<br>T <sup>(2)</sup> | HEIGHT TO<br>CENTRE<br>M | HEIGHT<br>TO EAVE<br>M | NOM.<br>DIAMETER<br>M | OUTLET<br>HEIGHT<br>MM <sup>(6)</sup> | BOTTOM<br>OUTLET<br>MM | CONE<br>ANGLE | AUGER<br>LENGTH<br>M (FT) <sup>(3)</sup> | WIDE<br>LOAD<br>PILOTS <sup>(4)</sup> | SILOS<br>PER<br>TRUCK <sup>(5)</sup> | CENTRE<br>FILL DIA<br>MM | FOOTING<br>PLAN<br>STYLE |
|-----------|----------------------------|---------------------------------------|---------------------------------|--------------------------|------------------------|-----------------------|---------------------------------------|------------------------|---------------|------------------------------------------|---------------------------------------|--------------------------------------|--------------------------|--------------------------|
| K431S     | 31                         | 25                                    | 28                              | 5.9                      | 5.0                    | 3.1                   | 600                                   | 200                    | 35°           | 10.2 (34')                               | None                                  | 2                                    | 500                      | 4 LEG                    |
| K448S     | 48                         | 38                                    | 44                              | 6.1                      | 5.0                    | 3.8                   | 500                                   | 200                    | 31°           | 10.5 (35')                               | 1                                     | 2                                    | 500                      | 4 LEG                    |
| K458S     | 58                         | 47                                    | 53                              | 6.9                      | 5.8                    | 3.8                   | 500                                   | 200                    | 31°           | 11.9 (40')                               | 1                                     | 2                                    | 500                      | 4 LEG                    |
| K481S     | 81                         | 65                                    | 75                              | 8.1                      | 6.9                    | 4.2                   | 600                                   | 250                    | 35°           | 13.8 (45')                               | 1                                     | 2                                    | 610                      | ROUND                    |
| K492S     | 92                         | 73                                    | 85                              | 8.9                      | 7.7                    | 4.2                   | 600                                   | 250                    | 35°           | 15.2 (50')                               | 1                                     | 1                                    | 610                      | ROUND                    |
| K486S     | 86                         | 69                                    | 79                              | 7.7                      | 6.4                    | 4.6                   | 600                                   | 250                    | 35°           | 13.2 (43')                               | 2                                     | 1                                    | 610                      | ROUND                    |
| K4100S    | 100                        | 81                                    | 92                              | 8.6                      | 7.3                    | 4.6                   | 600                                   | 250                    | 35°           | 14.7 (48')                               | 2                                     | 1                                    | 610                      | ROUND                    |
| K4114S    | 114                        | 93                                    | 105                             | 9.4                      | 8.1                    | 4.6                   | 600                                   | 250                    | 35°           | 16.0 (53')                               | 2                                     | 1                                    | 610                      | ROUND                    |
| K4128S    | 128                        | 104                                   | 118                             | 10.3                     | 9.0                    | 4.6                   | 600                                   | 250                    | 35°           | 18.0 (60')                               | 2                                     | 1                                    | 610                      | ROUND                    |
| K4188EGS* | 189                        | 153                                   | 174                             | 14.3                     | 13.0                   | 4.6                   | 700                                   | 250                    | 45°           | 23.8 (78')                               | 2                                     | 1                                    | 610                      | ROUND                    |
| K4208EGS  | 208                        | 168                                   | 191                             | 15.4                     | 14.1                   | 4.6                   | 700                                   | 250                    | 45°           | 25.5 (84')                               | 2                                     | 1                                    | 610                      | ROUND                    |
| K4129S*   | 129                        | 104                                   | 118                             | 9.5                      | 8.2                    | 4.9                   | 600                                   | 250                    | 35°           | 16.0 (53')                               | 2                                     | 1                                    | 610                      | ROUND                    |
| K4144S*   | 144                        | 117                                   | 132                             | 10.5                     | 9.1                    | 4.9                   | 600                                   | 250                    | 35°           | 18.0 (60')                               | 2                                     | 1                                    | 610                      | ROUND                    |
| K4190EGS* | 190                        | 154                                   | 175                             | 13.4                     | 12.0                   | 4.9                   | 700                                   | 250                    | 45°           | 22.4 (74')                               | 2                                     | 1                                    | 610                      | ROUND                    |
| K4211EGS  | 211                        | 171                                   | 194                             | 14.5                     | 13.1                   | 4.9                   | 700                                   | 250                    | 45°           | 24.1 (79')                               | 2                                     | 1                                    | 610                      | ROUND                    |
| K4232EGS  | 232                        | 188                                   | 213                             | 15.8                     | 14.4                   | 4.9                   | 700                                   | 250                    | 45°           | 26.0 (85')                               | 2                                     | 1                                    | 610                      | ROUND                    |

SPECIFICATIONS (TOOWOOMBA) Effective 14 August 2025

| MODEL    | CAPACITY<br>M <sup>3</sup> | CAPACITY<br>WHEAT<br>T <sup>(1)</sup> | MAX<br>LOAD<br>T <sup>(2)</sup> | HEIGHT TO<br>CENTRE<br>M | HEIGHT<br>TO EAVE<br>M | NOM.<br>DIAMETER<br>M | OUTLET<br>HEIGHT<br>MM <sup>(6)</sup> | BOTTOM<br>OUTLET<br>MM | CONE<br>ANGLE | AUGER<br>LENGTH<br>M (FT) <sup>(3)</sup> | WIDE<br>LOAD<br>PILOTS <sup>(4)</sup> | SILOS<br>PER<br>TRUCK <sup>(5)</sup> | CENTRE<br>FILL DIA<br>(MM) | FOOTING<br>PLAN<br>STYLE |
|----------|----------------------------|---------------------------------------|---------------------------------|--------------------------|------------------------|-----------------------|---------------------------------------|------------------------|---------------|------------------------------------------|---------------------------------------|--------------------------------------|----------------------------|--------------------------|
| K437EGS  | 37                         | 30                                    | 34                              | 6.2                      | 5.2                    | 3.4                   | 700                                   | 200                    | 35°           | 11.2 (37')                               | 1                                     | 2                                    | 500                        | 4 LEG                    |
| K448EGS  | 48                         | 39                                    | 44                              | 7.3                      | 6.3                    | 3.4                   | 700                                   | 200                    | 35°           | 12.9 (42')                               | 1                                     | 2                                    | 500                        | 4 LEG                    |
| K457EGS  | 58                         | 47                                    | 53                              | 8.4                      | 7.4                    | 3.4                   | 700                                   | 200                    | 35°           | 14.6 (48')                               | 1                                     | 1                                    | 500                        | 4 LEG                    |
| K468EGS  | 68                         | 55                                    | 63                              | 9.5                      | 8.5                    | 3.4                   | 700                                   | 200                    | 35°           | 16.3 (54')                               | 1                                     | 1                                    | 500                        | 4 LEG                    |
| K480EGS  | 80                         | 65                                    | 74                              | 11.1                     | 10.1                   | 3.4                   | 700                                   | 200                    | 45°           | 18.8 (62')                               | 1                                     | 1                                    | 500                        | 4 LEG                    |
| K447EGS  | 48                         | 39                                    | 44                              | 6.4                      | 5.3                    | 3.8                   | 700                                   | 200                    | 35°           | 11.5 (38')                               | 1                                     | 2                                    | 500                        | 4 LEG                    |
| K460EGS  | 60                         | 49                                    | 56                              | 7.5                      | 6.4                    | 3.8                   | 700                                   | 200                    | 35°           | 13.2 (43')                               | 1                                     | 2                                    | 500                        | 4 LEG                    |
| K473EGS  | 73                         | 59                                    | 67                              | 8.7                      | 7.6                    | 3.8                   | 700                                   | 200                    | 35°           | 15.1 (50')                               | 1                                     | 1                                    | 500                        | 4 LEG                    |
| K486EGS  | 86                         | 70                                    | 79                              | 9.8                      | 8.7                    | 3.8                   | 700                                   | 200                    | 35°           | 16.8 (55')                               | 1                                     | 1                                    | 500                        | 4 LEG                    |
| K4101EGS | 101                        | 82                                    | 93                              | 11.4                     | 10.3                   | 3.8                   | 700                                   | 200                    | 45°           | 19.3 (63')                               | 1                                     | 1                                    | 500                        | 4 LEG                    |
| K458EGS  | 58                         | 47                                    | 53                              | 6.6                      | 5.4                    | 4.2                   | 700                                   | 250                    | 35°           | 11.8 (39')                               | 1                                     | 2                                    | 610                        | ROUND                    |
| K472EGS  | 73                         | 59                                    | 67                              | 7.7                      | 6.5                    | 4.2                   | 700                                   | 250                    | 35°           | 13.5 (44')                               | 1                                     | 2                                    | 610                        | ROUND                    |
| K488EGS  | 88                         | 72                                    | 81                              | 8.9                      | 7.7                    | 4.2                   | 700                                   | 250                    | 35°           | 15.4 (51')                               | 1                                     | 1                                    | 610                        | ROUND                    |
| K4104EGS | 104                        | 84                                    | 95                              | 10                       | 8.8                    | 4.2                   | 700                                   | 250                    | 35°           | 17.1 (56')                               | 1                                     | 1                                    | 610                        | ROUND                    |
| K4122EGS | 122                        | 99                                    | 112                             | 11.7                     | 10.5                   | 4.2                   | 700                                   | 250                    | 45°           | 19.8 (65')                               | 1                                     | 1                                    | 610                        | ROUND                    |
| K4137EGS | 137                        | 111                                   | 126                             | 12.8                     | 11.6                   | 4.2                   | 700                                   | 250                    | 45°           | 21.5 (70')                               | 1                                     | 1                                    | 610                        | ROUND                    |
| K483EGS  | 83                         | 67                                    | 76                              | 7.9                      | 6.6                    | 4.4                   | 700                                   | 250                    | 35°           | 13.8 (45')                               | 1                                     | 2                                    | 610                        | ROUND                    |
| K499EGS  | 100                        | 81                                    | 92                              | 9.0                      | 7.8                    | 4.4                   | 700                                   | 250                    | 35°           | 15.6 (51')                               | 1                                     | 1                                    | 610                        | ROUND                    |
| K4117EGS | 117                        | 95                                    | 108                             | 10.1                     | 8.9                    | 4.4                   | 700                                   | 250                    | 35°           | 17.3 (57')                               | 1                                     | 1                                    | 610                        | ROUND                    |
| K4138EGS | 138                        | 112                                   | 127                             | 11.9                     | 10.6                   | 4.4                   | 700                                   | 250                    | 45°           | 20.1 (66')                               | 1                                     | 1                                    | 610                        | ROUND                    |
| K4155EGS | 155                        | 125                                   | 142                             | 13.0                     | 11.7                   | 4.4                   | 700                                   | 250                    | 45°           | 21.8 (72')                               | 1                                     | 1                                    | 610                        | ROUND                    |
| K471EGS  | 73                         | 59                                    | 67                              | 6.9                      | 5.6                    | 4.6                   | 700                                   | 250                    | 35°           | 12.3 (40')                               | 2                                     | 1                                    | 610                        | ROUND                    |
| K491EGS  | 91                         | 74                                    | 84                              | 8.0                      | 6.7                    | 4.6                   | 700                                   | 250                    | 35°           | 14.0 (46')                               | 2                                     | 2                                    | 610                        | ROUND                    |
| K4110EGS | 110                        | 89                                    | 101                             | 9.2                      | 7.8                    | 4.6                   | 700                                   | 250                    | 35°           | 15.9 (52')                               | 2                                     | 1                                    | 610                        | ROUND                    |
| K4129EGS | 129                        | 104                                   | 118                             | 10.3                     | 8.9                    | 4.6                   | 700                                   | 250                    | 35°           | 17.6 (58')                               | 2                                     | 1                                    | 610                        | ROUND                    |
| K4151EGS | 151                        | 123                                   | 139                             | 12.0                     | 10.7                   | 4.6                   | 700                                   | 250                    | 45°           | 20.2 (66')                               | 2                                     | 1                                    | 610                        | ROUND                    |
| K4170EGS | 170                        | 138                                   | 156                             | 13.2                     | 11.8                   | 4.6                   | 700                                   | 250                    | 45°           | 22.1 (73')                               | 2                                     | 1                                    | 610                        | ROUND                    |
| K4188EGS | 189                        | 153                                   | 174                             | 14.3                     | 13.0                   | 4.6                   | 700                                   | 250                    | 45°           | 23.8 (78')                               | 2                                     | 1                                    | 610                        | ROUND                    |

SPECIFICATIONS (TOOWOOMBA) Effective 14 August 2025

| Splayed Leg Base | MODEL     | CAPACITY<br>M <sup>3</sup> | CAPACITY<br>WHEAT<br>T <sup>(1)</sup> | MAX<br>LOAD<br>T <sup>(2)</sup> | HEIGHT<br>TO<br>CENTRE<br>M | HEIGHT<br>TO EAVE<br>M | NOM.<br>DIAMETER<br>M | OUTLET<br>HEIGHT<br>MM <sup>(6)</sup> | BOTTOM<br>OUTLET<br>MM | CONE<br>ANGLE | AUGER<br>LENGTH<br>M (FT) <sup>(3)</sup> | WIDE<br>LOAD<br>PILOTS <sup>(4)</sup> | SILOS<br>PER<br>TRUCK <sup>(5)</sup> | CENTRE<br>FILL DIA<br>(MM) | FOOTING<br>PLAN<br>STYLE |
|------------------|-----------|----------------------------|---------------------------------------|---------------------------------|-----------------------------|------------------------|-----------------------|---------------------------------------|------------------------|---------------|------------------------------------------|---------------------------------------|--------------------------------------|----------------------------|--------------------------|
|                  | K4208EGS  | 208                        | 168                                   | 191                             | 15.4                        | 14.1                   | 4.6                   | 700                                   | 250                    | 45°           | 25.5 (84')                               | 2                                     | 1                                    | 610                        | ROUND                    |
|                  | K4102EGS  | 102                        | 83                                    | 94                              | 8.2                         | 6.8                    | 4.9                   | 700                                   | 250                    | 35°           | 14.3 (47')                               | 2                                     | 1                                    | 610                        | ROUND                    |
|                  | K4123EGS  | 123                        | 100                                   | 113                             | 9.3                         | 7.9                    | 4.9                   | 700                                   | 250                    | 35°           | 16.0 (53')                               | 2                                     | 1                                    | 610                        | ROUND                    |
|                  | K4144EGS  | 144                        | 117                                   | 133                             | 10.4                        | 9.0                    | 4.9                   | 700                                   | 250                    | 35°           | 17.7 (58')                               | 2                                     | 1                                    | 610                        | ROUND                    |
|                  | K4169EGS  | 169                        | 137                                   | 156                             | 12.2                        | 10.8                   | 4.9                   | 700                                   | 250                    | 45°           | 20.5 (67')                               | 2                                     | 1                                    | 610                        | ROUND                    |
|                  | K4190EGS* | 190                        | 154                                   | 175                             | 13.4                        | 12.0                   | 4.9                   | 700                                   | 250                    | 45°           | 22.4 (74')                               | 2                                     | 1                                    | 610                        | ROUND                    |
|                  | K4211EGS* | 211                        | 171                                   | 194                             | 14.5                        | 13.1                   | 4.9                   | 700                                   | 250                    | 45°           | 24.1 (79')                               | 2                                     | 1                                    | 610                        | ROUND                    |
|                  | K4232EGS* | 232                        | 188                                   | 213                             | 15.6                        | 14.2                   | 4.9                   | 700                                   | 250                    | 45°           | 26.0 (85')                               | 2                                     | 1                                    | 610                        | ROUND                    |

1 - Wheat capacity based on typical consolidated/compacted bulk density in silo. 2 - Max. Load based on engineering design. This may not apply to products other than grain. 3 - Auger lengths are indicative only and are based on 40° angle. 4 - Pilot/Escort vehicle requirements may vary in certain locations (e.g. metropolitan areas). 5 - Number of silos that can be transported per delivery - subject to availability of transport equipment. \* Purchase of this model is contingent to Kotzur being able to obtain an oversize permit for the route required to deliver this model. 6 - Nominal outlet height only.

Actual tonnage capacity achieved in silos will vary according to a number of factors including bulk density (test weight), angle of repose and headspace volume (for aeration).



WARRANTY - Kotzur Pty Ltd are confident in the quality of the products they design, manufacture and supply.

The following warranties apply:

- Structures including footings, elevator towers, walkways, silos etc - 5 years.
- Mechanical equipment including conveyors but excluding drive motors - 12 months.
- OEM equipment including drive motors and gearboxes - supplier warranty (generally 3 months).

This guarantee covers faulty design, engineering and workmanship; however this does not include problems arising from factors over which Kotzur has no control. These factors include footings constructed by others, negligent damage, unintended use of products, poor maintenance or care, normal wear and tear. Equipment manufactured by others and brought in by Kotzur Pty Ltd (e.g. Silo unloaders, aeration equipment) carry their respective manufacturers warranty. Please note this warranty excludes consequential losses.



**WALLA WALLA**

60 Commercial Street  
Walla Walla, NSW 2659

☎ 02 6029 4700

✉ [info@kotzur.com](mailto:info@kotzur.com)

**TOOWOOMBA**

97 Steger Road  
Charlton, QLD 4350

☎ 07 4634 4622

✉ [enquiry@kotzur.com](mailto:enquiry@kotzur.com)

**PERTH**

44 Oliver Street  
Northam, WA 6401

☎ 08 9495 3000

✉ [info@kotzur.com](mailto:info@kotzur.com)



**[www.kotzur.com](http://www.kotzur.com)**