

TRANSPORTABLE UNSEALED STORAGE SILOS







APPLICATION

Short term grain storage.

Storage of grains which are not susceptible to insect pests.

Unsealed silos are not recommended where insect pests present a risk. Ask for further information on the importance of sealed silos in the drive to control insects and maintain grain free of chemical residue.

FEATURES

- Fully factory assembled and delivered ready to use.
- **-** Zincalume walls/roof and galvanised hopper/support structure.
- Ground operated centre lid opening.
- Optional roof side inspection hatches lock down with spring catch.
- Lever operated outlet slide gate.
- All silo models can be tailored to specific customer requirements.
- Covered by Kotzur 5 year warranty.







SPECIFICATIONS Effective 1 October 2024

N	MODEL	CAPACITY M³	CAPACITY WHEAT T ⁽¹⁾	MAX LOAD T ⁽²⁾	HEIGHT TO CENTRE M	HEIGHT TO EAVE M	NOM. DIAMETER M	OUTLET HEIGHT MM ⁽⁵⁾	BOTTOM OUTLET MM	CONE ANGLE	AUGER LENGTH M (FT) ⁽³⁾	FOOTING PLAN STYLE	WIDE LOAD PILOTS ⁽⁴⁾	SILOS PER TRUCK ⁽⁶⁾
	K431	31	25	28	5.9	5.0	3.1	500 ⁽⁵⁾	200	32/42°	10.2 (34')	4 LEG	None	2
	K448	48	39	44	6.1	5.0	3.8	500 ⁽⁵⁾	200	31°	10.5 (35')	4 LEG	1	2
	K458	58	47	53	6.9	5.8	3.8	500(5)	200	31°	11.9 (40')	4 LEG	1	2
	K481	81	65	74	8.1	6.9	4.2	600	250	35⁰	13.8 (45')	ROUND	1	2

^{1 -} Wheat capacity based on typical consolidated/compacted bulk density in silo. 2 - Max load based on engineering design. This may not apply to products other than grain. 3 - Auger lengths are indicative only and are based on 40° angle. 4 - Pilot/escort vehicle requirements may vary in certain locations (e.g. metropolitan areas). 5 - Nominal outlet height only. 6 - Number of silos that can be transported per delivery.

FEATURES/OPTIONS

STD - Standard

OPT – Optional

N/A - Not Available

MODEL	CENTRE FILL DIA MM	ROOF SIDE INSPECTION HOLE ⁽¹⁾	SIGHT GLASS LEVEL INDICATION	EXTERNAL WALL ROOF LADDER & CAGE	REMOTE OPENING AUTO RESEALING	BASE MANHOLE	AERATION	WHITE COLORBOND WALLS/ROOF	BAGGING CHUTE
K431	500	OPT	STD ^(A)	OPT	STD	STD	OPT	OPT	STD
K448	500	OPT	STD ^(A)	OPT	STD	STD	OPT	OPT	STD
K458	500	OPT	STD ^(A)	OPT	STD	STD	OPT	OPT	STD
K481	610	OPT	STD ^(B)	OPT	STD	STD	OPT	OPT	N/A

^{1 -} Due to OHS regulations, from Jan 2003 roof manhole and internal ladder are no longer supplied. A - One sight glass is standard in each ring. Additional sight glasses are optional. B - One sight glass is standard in each ring plus one additional sight glass high in top ring.

WARRANTY - Kotzur Pty Ltd are confident in the quality of the products they design, manufacture and supply.

The following warranties apply:

- Structures including footings, elevator towers, walkways, silos etc 5 years.
- Mechanical equipment including conveyors but excluding drive motors 12 months.
- OEM equipment including drive motors and gearboxes supplier warranty (generally 3 months).

This guarantee covers faulty design, engineering and workmanship; however this does not include problems arising from factors over which Kotzur has no control. These factors include footings constructed by others, negligent damage, unintended use of products, poor maintenance or care, normal wear and tear. Equipment manufactured by others and brought in by Kotzur Pty Ltd (e.g. Silo unloaders, aeration equipment) carry their respective manufacturers warranty. Please note this warranty excludes consequential losses.

WALLA WALLA

60 Commercial Street Walla Walla, NSW 2659



info@kotzur.com

TOOWOOMBA

97 Steger Road Charlton, QLD 4350

**** 07 4634 4622

enquiry@kotzur.com

PERTH

Unit 3/35 Gillam Drive Kelmscott, WA 6111



