

# ELEVATED SEED SILOS



## **APPLICATION**

family wned ustralian

Storage of small quantities of grain

Storage of grain to be emptied into bags, buckets or grain cart

Sealed silos are recommended where insect pests present a risk. Ask for further information on the importance of sealed silos in the drive to control insects and maintain grain free of chemical residue

## **FEATURES**

- Fully factory assembled and delivered ready to use
- Zincalume walls/roof and galvanized hopper/support structure
- Open front with offset cone for easy access to empty
- Roof hatches lock down with spring catch
- Raised outlet for convenient bagging with standard bagging chute
- Ground operated centre lid opening
- All silo models can be varied/modified to specific customer requirements
- Covered by Kotzur 5 year warranty.

#### **SPECIFICATIONS** Effective 14 June 2022

MODEL	CAPACITY M <sup>3</sup>	CAPACITY WHEAT <sup>®</sup> T	MAY	HEIGHT TO CENTRE M	псічпі	NOM. DIAMETER M	OUTLET HEIGHT MM	BOTTOM OUTLET MM	CONE ANGLE	AUGER LENGTH <sup>(3)</sup> M (FT)		WIDE LOAD PILOTS <sup>(4)</sup>
K4518	18	15	17	4.9	4.0	3.1	900	230	32/42°	8.3 (28')	4 LEG	None
K4524	24	19	22	5.8	4.9	3.1	900	230	32/42°	9.9 (33')	4 LEG	None

1 - Wheat capacity based on typical consolidated/compacted bulk density in silo. 2 - Max. Load based on engineering design. This may not apply to products other than grain. 3 - Auger lengths are indicative only and are based on 40° angle. 4 - Pilot/Escort vehicle requirements may vary in certain locations (e.g. metropolitan areas).

#### **FEATURES/OPTIONS**

STD - Standard OPT - Optional N/A - Not Available

MODEL	CENTRE FILL DIA (MM)	ROOF SIDE INSPECTION HOLE <sup>(1)</sup>	SIGHT GLASS LEVEL <sup>(2)</sup> INDICATION	EXTERNAL WALL ROOF LADDER & CAGE	REMOTE OPENING STANDARD	BASE MANHOLE	AERATION	WHITE COLORBOND WALLS ROOF	BAGGING CHUTE	SLIDE GATE	SEALED GASTIGHT
K4518	500	OPT	STD	OPT	STD	STD	OPT	OPT	STD	OPT	OPT
K4524	500	OPT	STD	OPT	STD	STD	OPT	OPT	STD	OPT	OPT

1 - Due to OHS regulations, from Jan 2003 roof manhole and internal ladder are no longer supplied. 2 - One Sight Glass is standard in each ring. Additional Sight Glasses are optional.

WARRANTY - Kotzur Pty Ltd are confident in the quality of the products they design, manufacture and supply. The company guarantees its product for a period of five years from date of purchase. This guarantee covers faulty design, engineering and workmanship however does not include problems arising from factors over which they have no control. These factors include footings constructed by others, negligent damage, unintended use of products, poor maintenance of care, normal wear and tear. Please note that this warranty excludes Consequential losses.

Whilst every care has been made in the preparation of this brochure, the company does not accept responsibility for inadvertent errors. It reserves the right to make changes and improvements to its products without further notice 14/06/2022

f



